

UTG GEN III Blank-Firing Adapter

IMPORTANT!

Before installation, ensure firearm is clear before attaching blank-firing adapter.

NOTES


This model blank-firing adapter is intended for use with the .223/5.56mm A1 or A2 flash hider only.



- Blank-firing adapter for .223 rifles with a 20" barrel is RED (p/n BFA-MIL223R) – *discontinued in 2017*.
- Blank-firing adapter for .223 Model 4 ("M4") carbines with a 16" barrel is YELLOW (p/n BFA-MIL223Y).
- Use only B223M200FX (M200A) blank ammunition with these adapters. **DO NOT** use M200A1 "Hollywood .223" blanks as this could cause serious damage to firearm and operator.
- **DO NOT** use with live ammunition.
- Every 50 rounds, check to ensure the adapter is still hand-tight and secure.
- Clean carbon build-up after each use.
- **DO NOT** use tool to tighten the adapter. **Hand-tighten ONLY.**

INSTALLATION

1. Unscrew the bolt and slide it all the way out.



2. Hook the adapter into the first groove of the flash hider.



3. Slide the bolt into the flash hider and **HAND TIGHTEN**.

DO NOT use any tool to tighten.



www.bolandfx.com

PHONE: (863) 324-7784

E-Mail: customerservice@bolandfx.com